



## DESCRIPTION

All for Stone™ XtremeClean™ is a fast acting concentrated high alkaline cleaner and degreaser. It is designed to remove most wax, grease, oil, light soap scum, mildew and algae. Effectively removes most factory applied waxes, floor finishes and is ideal for areas that have been neglected or subject to heavy use.

## USES

Use on all natural stone, grout, ceramic, porcelain, terracotta, saltillo, quarry tiles, terrazzo, concrete, pavers, masonry and other water safe surfaces.

## TEST FIRST

Due to the nature of different surfaces, you should do several test areas in inconspicuous areas according to the label instructions to determine surface colour stability and desired results. The end user must determine the suitability of the product for their intended use.

## PRECAUTIONS

1. DO NOT KNEEL IN THIS PRODUCT, AVOID ALL SKIN CONTACT;
2. Always Test first;
3. Read entire label and product technical bulletin before using;
4. Wear appropriate skin and eye protection;
5. Use when surface temperature is between 4°C and 32°C.

## INSTRUCTIONS

1. Sweep, vacuum, or wipe surface;
2. Dilute Xtreme Clean™ as follows:
  - a) LIGHT: Mix 10 parts water to 1 part product;
  - b) MODERATE: Mix 5 parts water to 1 part product;
  - c) HEAVY: Mix 3 parts water to 1 part product;
  - d) STRIPPING WAX: Mix 2 parts water to 1 part product;
3. Carefully apply the solution to pre-wet surface with a sponge or a mop;
4. Allow minimum dwell time of 3-5 minutes for cleaning or 10 minutes for stripping - DO NOT ALLOW THE PRODUCT TO DRY ON THE SURFACE;
5. Scrub with a white nylon pad, scrub brush or scrub machine;
6. Remove the dirty solution with a wet vac or mop;
7. Rinse thoroughly with clean water;
8. Repeat the process as necessary.

## LIMITATIONS

- Do not allow product to come in contact with any non-recommended surfaces.
- Regular use of high alkaline cleaners will affect the performance of sealers.

## COVERAGE

Approximately 10–35 square meters per litre. The coverage will vary depending on density, porosity, texture, surface absorption, weather, time solution left on surface, the application method, severity of the problem and dilution used.

## HANDLING AND STORAGE

- Close container tightly after each use.
- Store in original container only.
- Store in temperatures between 4°C and 32°C.

## FIRST AID

If swallowed, do NOT induce vomiting. If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor, or for at least 15 minutes. If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If irritation persists, seek medical attention.

**SAFETY DIRECTIONS:** Avoid contact with skin and eyes.

### WARNING: Corrosive

R35 Causes severe burns

S1/2 Keep locked up and out of the reach of children

S26 In case of contact with eyes rinse immediately with plenty of water and seek medical advice

S37/39 Wear suitable gloves and eye/face protection

S45 In case of accident or if you feel unwell, seek medical advice immediately (show the label if possible)

## WARRANTY

All For Stone™ "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use. ALWAYS DO A TEST FIRST.